



Go safely back into public spaces.



Connect with doors, gates, peripheral devices & network



SPECIFICATIONS

| | |
|--|--|
| Screen | |
| Size | 8.0" IPS LCD screen |
| Resolution | 800x1280 |
| Design | Industrial-grade, waterproof, dustproof & vandal-proof |
| Processor | |
| CPU | Qualcomm Snapdragon Octa-Core Processor |
| CPU (Optional) | Rockchip RK3288 Quad-Core |
| System | Android 7.1.2 |
| Storage | EMMC 8 GB |
| Camera | |
| Resolution | 2 million pixels |
| Type | Binocular vision wide dynamic camera |
| Aperture | F2.4 |
| Focusing Distance | 19.6" - 60" |
| White Balance | Auto |
| Photo Flood Light | LED and IR dual photo flood light |
| Infrared Thermal Imaging Module | |
| Temperature Detection | Available |
| Temperature Detection Distance | 3.2' (optimal distance 1.6') |
| Temperature Measurement Accuracy | ±0.9 °F |
| Temperature Measurement Range | 50 °F - 107.6 °F |
| Thermal Field of View | 89.6 x 89.6 ° |
| Elevated Temperature Alarm | Supported (temperature alarm value can be set) |
| Interfaces | |
| Network Module | Ethernet (RJ-45) and Wireless (Wi-Fi) |
| Audio | 2.5W / 4R speakers |
| USB | 1 USB OTG, 1USB HOST standard A port |

| | |
|--|---|
| Serial Communication | 1 RS232 serial port |
| Relay Output | 1 door open signal output |
| Wiegand | 1 Wiegand 26/34 output and input |
| Upgrade Button | Supports USB boot upgrade button |
| Access Control | |
| Facial Recognition based Access Control | 1:1 & N:1 face recognition |
| Face Mask Detection based Access Control | Available |
| Elevated Temperature based Access Control | Available |
| ID Card based Access Control | Optional IC card, S50, NTAG, CPU, DESfire |
| Barcode Reader based Access Control | Optional Barcode, 2D Barcode & QR Code Reader |
| Call Receptionist / Security to Grant Access | Available |
| Call IT / Screen Skills Guru for Support | Available |
| Face Library | Up to 30,000 |
| Remote Management | |
| Attendance Tracking & Reporting | Available |
| User Interface Customization | Available |
| Remote Device Management | Available |
| Remote Database Management | Available |
| Remote Firmware Upgrade | Available |
| System | |
| Power | DC 12V |
| Operating Temperature | 0 °F - 140 °F |
| Power Consumption | 13.5W Max |
| Installation Method | Wall Mount, Table Stand & Floor Stand |
| Product Size | 11.66" x 5.23" x 0.98" |
| What's in the Box | OneScreen GoSafe, Power Adapter, User Manual |